



Active Online



Elegant access solutions.

Residential Series: IP intercom door station with 2.0MP camera

This Residential Series video intercom door stations is single channel, ideal for homes & single-premises buildings. The door stations features a 2.0MP camera with auto day/night IRC, all in a stylish aluminium body.

- 1/2.8" 2.0MP 1.95mm lens camera with 160° FOV
- Built-in microphone and speaker for 2-way talk
- Connect with intercom monitor(s) via Ethernet
- Intuitive, easy-to-use interface
- Alarm and RS485 input/output relays
- Power via 12VDC or Power over Ethernet (802.3af)
- Weather & vandal resistant IP55/IK07 aluminium body
- Flush and surface mount installation options



Single Button Door Contact






Remote Access & Answer via App



Weather & Vandal Resistant

Residential Door Station | Series Specifications

Model		INTIPRDSG
General	Product Image	
	Main Processor	Embedded Microprocessor
	Camera System	1/2.8" 2.0 Megapixel CMOS with 1.95mm lens (Horizontal FoV: 160°)
	Low-Light Application	Day/Night ICR
	Card Support	N/A
	Keypad	1 Mechanical Button
	Tamper Detection	Yes
	Input / Output	1 x alarm input / 1 x alarm output / 1 x RS485
	Audio / 2-Way Talk	Omni-directional Microphone & Embedded Loudspeaker for 2-way talk
	Internal MicroSD Slot	Yes, up to 64GB
	Ethernet / Network	10M/100Mbps Self-adaptive / TCP/IP protocol
	Max. Additional Door Stations	20
	Max. Indoor Monitors	10
	App Connection	QR Code
Environmental	Vandal Resistant	IK07
	Ingress Protection	IP55
	Installation Options	Supports surface box and flush box mount
	Construction	Aluminium
	Installation Kit	N/A
	Power Input / Use	12VDC 1A, PoE (802.3af) / Operation < 12W
	Weight / Dimensions	0.80kg / 182 x 101 x 30mm
Accessories	Product Diagram	
	Mounting Options	 <p>Flush Box Mount (INTIPRDSG-FB) / Surface Box Mount (INTIPADSG-SB)</p>

Your local VIP Vision™ IP solutions professional:

www.activeonline.com.au 1300 816 742