



3-in-1 deterrence solution


Professional AI Series: Fixed lens AI active deterrence turrets in 6.0MP and 8.0MP

The Professional AI Series utilises the latest in AI machine learning technology to identify people & vehicles with superior accuracy and reliability. The active deterrence range incorporates AI detection and a variety of in-camera features to deter intruders. Upon a human or vehicle detection event, these cameras can trigger a white LED spotlight for security lighting, a flashing blue/red LED strobe and a loud siren with programmable message/tone, to deter intruders. Quickly search and track people & vehicles across all Acupick CCTV cameras in your security system.


- Stream up to 8.0MP (3840 x 2160) at 25fps
- Intelligent search across all Acupick cameras
- Activates spotlight, flashing light & siren, switching from IR to colour footage in response to alarm events
- 24/7 Colour low light footage as low as 0.004lx
- Up to 30m infrared, BLC/HLC & true WDR (120dB)
- Intelligent AI detection to identify people & vehicles
- Next-Gen Smart Motion Detection (SMD 4.0) & Perimeter Protection to prevent false alarms, using VIP Vision NVRs
- AI SSA detects/adjusts exposure to ensure clear video.




Spotlight, Siren & Blue/Red Strobe



Intelligent people & vehicle search



AI Adapts Scene for Best Picture

Specifications		6.0MP Fixed AI Deterrence Turret	8.0MP Fixed AI Deterrence Turret
Camera	Ordering Information	VSIPP-6DG-ID4	
	Image Sensor	1/2.7" 6.0MP Progressive Scan CMOS	1/2.7" 8.0MP Progressive Scan CMOS
	Effective Pixels	3072 (H) x 2048 (V)	3840 (H) x 2160 (V)
	RAM / ROM	2G / 256MB	
	Min Illumination	0.005 Lux/F1.4 (Color, 30 IRE), 0.0005 lux/F1.4 (B/W, 30 IRE), 0 lux (IR)	0.004 Lux/F1.0 (Color), 0.0004 lux/F1.0 (B/W, 30 IRE), 0 lux (IR)
	Electronic Shutter	1/3 ~ 1/100,000s	
	S/N Ratio	> 56dB	
	Infrared System	1 x Infrared LED, 30m range, Auto/manual on/off control	
	LED Illumination	1 x Spotlight (Warm White), 1 x Red & Blue Alarm Light	
Lens	Lens / Iris	2.8mm F1.0 Fixed Lens	
	Field of View	Horizontal: 97°, Vertical: 70°, Diagonal: 128°	Horizontal: 106°, Vertical: 55°, Diagonal: 125°
	Focus	Auto Focus / 1.5m Min. Focus Distance	
DORI	Detect (25px/m)	66m	
	Observe (63px/m)	26m	
	Recognise (125px/m)	13m	
	Identify (250px/m)	7m	
Video	Resolution	6.0MP (3072 x 2048) to CIF (352 x 288/352 x 240)	8.0MP (3840 x 2160) to CIF (352 x 288/352 x 240)
	Frame Rate	Main	6.0MP (1 ~ 25fps)
		Sub	704 x 576 (1 ~ 25fps)
		Third	1080p (1 ~ 25fps)
	Video Compression	H.265+ / H.265 / H.264+ / H.264 / H.264B / MJPEG	
	Bit Rate	H.265: 3 ~ 16384Kbps / H.264: 3 ~ 16384Kbps	
	Bit Rate Control	Constant Bit Rate (CBR) / Variable Bit Rate (VBR) / Average Bit Rate (ABR)	
	Day/Night	Auto (ICR) / Colour / B&W	
	Lighting Compensation	BLC / HLC / WDR (120dB)	
	Smart Scene Adaptive	SSA	
	White Balance	Auto / Natural / Street Lamp / Outdoor / Manual / Regional Custom	
	Gain Control	Auto	
	Noise Reduction	3D DNR	
	Picture Control	Mirror / Flip (0°, 90°, 180°, 270°)	
IVS	Video Functions	Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Illumination, Defog, Object Abandoned / Missing	
	Event Triggers	Motion Detection, Perimeter Protection, Video Tampering, Scene Changing, Network Disconnection, IP Address Conflict, Illegal Access, Storage Anomaly	
	AI Functions	Perimeter Protection: People and vehicle detection using tripwire or intrusion rules Loitering detection: People gathering and parking detection Acupick: Search by people/vehicle attribute (e.g colour) and track their movements	
	Intelligent search	Search people or vehicle detection events (Perimeter Protection), Search by attributes, such as clothing/vehicle colour and vehicle type (AI Quick Pick)	
Network	Ethernet	RJ-45 (10/100Base-T)	
	Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP, P2P	
	Streaming Method	Unicast / Multicast	
	Max. User Access	20 Users (Total bandwidth: 64MB)	
Interface	Video Interface	N/A	
	Audio Interface	Built-in Mic & Built-in Speaker, 1 Audio In/Output (RCA) / Audio Compression - PCM; G.711a; G.711Mu; G.726; G.723	
	Alarm Interface	1 channel in: 5mA 3-5VDC / 1 channel out: 300mA 12VDC	
	RS485	N/A	
	Edge Storage	MicroSD Card (up to 256GB) / NAS / FTP / SFTP	
	Interoperability	ONVIF (Profile S, Profile G, Profile T) / P2P / CGI / Milestone	
Environmental	Power Supply	12VDC / PoE	
	Power Consumption	< 8.6 W (12 VDC); < 10.1 W (PoE)	
	Operating Conditions	-40°C ~ +60°C / ≤95% RH	
	Ingress Protection	IP67	
	Vandal Resistance	N/A	
	Housing	Metal	
	Pan/Tilt/Rotation	Pan: 0° ~ 360°, Tilt: 0° ~ 78°, Rotation: 0° ~ 360°	
	Dimensions	Ø122mm x 111mm	
	Net Weight	0.75kg	
Accessories			Junction Box
			VSBKTA137 or VSBKTA130E
			Wall Mount
			VSBKTB205W-E or VSBKTB203W
			Ceiling Mount
			VSBKTA109 + VSBKTB220C
			Pole Mount
			VSBKTB205W-E + VSBKTA152E

Your local VIP Vision™ IP solutions professional:

www.activeonline.com.au 1300 816 742