



Auto-tracking solar security

Specialist AI Series: Solar 4G Multi-Vision PTZ Camera with Hybrid Zoom

Deliver AI surveillance to remote sites without power or hardwired network access using the standalone Multi-Vision PTZ camera from VIP Vision. It features a built-in 4G modem, monocrystalline solar panel and lithium battery. The camera combines a fixed turret for site overview with a Hybrid Zoom PTZ dome that automatically tracks people and vehicles. When detection events occur, it activates an LED spotlight and siren to deter intruders.

- 3.0MP@15fps 2.8mm wide angle overview camera
- 3.0MP@15fps PTZ dome with Hybrid Zoom - twin cameras switch focal lengths to zoom on subjects during AI auto-tracking of people & vehicles
- Activates LED & siren in response to AI detection
- 24/7 surveillance powered by 8W integrated solar panel and built-in 65Wh lithium battery
- Always-On Video provides continuous video recording at 1fps with low power consumption; AI wakes camera on event detection & boosts image capture to 15fps



Smart Person & Vehicle Detection



Spotlight & siren deters intruders



Quick Deploy 4G Camera

Specifications		3.0MP Solar 4G Fixed Turret & Pan-tilt unit
Camera	Ordering Information	VSIPSLR-3P3F
Image Sensor	3.0MP Fixed Lens Overview Camera	3.0MP Hybrid Zoom PTZ Dome Camera
Effective Pixels	1/2.8" 3.0MP Progressive Scan CMOS	Dual 1/2.8" 3.0MP Progressive Scan CMOS
RAM / ROM	2304 (H) x 1296 (V)	2304 (H) x 1296 (V)
Min Illumination	256 MB / 256 MB	0.0005 lux@F1.0 (Color, 30 IRE); 0 lux (Illuminator on)
S/N Ratio	>55 dB	
Lens	LED Illumination	4 x Spotlight (Warm White) 30m range
	Lens / Iris	3.6mm & 8.4mm F1.0 Fixed Lenses
DORI	Field of View	Horizontal: 94°, Vertical: 52°, Diagonal: 110°
	Focus	Auto Focus / 1.1m Min. Focus Distance
PTZ	Detect	4 x Spotlight (Warm White) 50m range
	Observe	3.6mm Lens: Horizontal: 82°, Vertical: 44°, Diagonal: 96°
	Recognise	8.4mm Lens: Horizontal: 15.1°, Vertical: 8.4°, Diagonal: 17.8°
	Identify	
Video	Pan / Tilt Range	N/A
	PTZ Speed	Pan: 0 ~ 350° (endless) / Tilt: -0 ~ 90°
	Modes / Presets	N/A
	Auto Tracking	Preset: Pan: 40°/s, Tilt: 40°/s, Manual: Pan: 40°/s, Tilt: 40°/s
	Resolution	N/A
	Frame Rate	Up to 50 presets / 8 Tour (32 presets per tour)
	Video Compression	3.0MP (2304 x 1296) to 640 x 360
	Bit Rate	3.0MP (2304 x 1296) to 640 x 360
	Bit Rate Control	3.0MP/1080p/720p/640 x 360 (15 fps)
IVS	Image Adjustments	Variable Bit Rate (VBR)
	Video Functions	Color and B&W Day/Night, Digital WDR, Auto Gain Control, Auto White Balance, 3D Noise Reduction, 180° Image Rotation
	AI Functions	Motion Detection
	Intelligent Search	AI People & Vehicle Detection via Smart Motion Detection (SMD 3.0)
Network	4G Carrier Frequency	Search via People or Vehicle Detection Events
	Transmission Power	B1/3/5/7/8/20/28 (FDD), B38/40/41 (TDD)
	Management Software	4G: Power Class 3: 23 dBm ± 2.7 dB
	Audio Interface	DMSS (Android & iOS)
	Alarm Linkage	Built-in Mic & Loudspeaker
	Edge Storage	Built-in White LED Spotlight & Deterrence Siren
	Power Supply	MicroSD card slot (up to 512GB), includes 128GB microSD card
Environmental	Power Consumption	65Wh lithium battery / 8W solar panel / Supports USB Type-C power supply
		Super Power Saving Mode: 40 mW (4G keep-alive)
		Always-on-Video Mode: 170 mW (1 frame every 2 seconds, SD card recording, 4G keep-alive)
		Performance Mode 1: 2.4 W (4G streaming, SD card recording, PTZ static, illuminator off)
		Performance Mode 2: 3.7 W (4G streaming, SD card recording, PTZ static, illuminator on)
	Operating Conditions	Max. Power Consumption: 8.0W (4G streaming, SD card recording, PTZ moving, illuminator on, speaker on)
	Protection	Camera & Solar Panel: -10 °C ~ +50 °C / ≤95% RH, battery: -20 °C ~ +60 °C / ≤95% RH
	Dimensions	IP66, TVS 2000V Lightning Proof, Surge Protection, Voltage Transient Protection
	Weight	223.2 mm x 130.0 mm x 215.0 mm
Application	Diagrams	1.8 kg

Your local VIP Vision™ IP solutions professional: